

# COPY

PATENT  
2922-102P

IN THE U.S. PATENT AND TRADEMARK OFFICE

APPLICANT: Je H. LEE et al.

SERIAL NO.: 09/118,824  
(Reissue of U.S. Patent No. 5,587,789)

FILED: July 20, 1998  
(Issued: December 24, 1996)

FOR: APPARATUS AND METHOD FOR CONTROLLING  
RECORDING AND REPRODUCTION IN DIGITAL  
VIDEO CASSETTE TAPE RECORDER



RECEIVED  
OCT -4 1999  
TC 2700 MAIL ROOM

## SUPPLEMENTAL REISSUE DECLARATION

Supplemental to the Reissue Declaration filed on July 20, 1998, Applicants hereby declare as follows:

That our names, residence and citizenship are indicated below;

That we hereby claim foreign priority benefits under Title 35, U.S.C. §119 of prior Korean application 58080/1996 filed on November 27, 1996; and

That every error in the patent which was corrected in the present reissue application, and is not covered by a prior oath/declaration submitted in this application, arose without any deceptive intention on the part of the Applicant.

The undersigned declares further that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements are made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and

Date: \_\_\_\_\_

Residence: Seoul, Korea  
Citizenship: Republic of Korea  
Address: 35-30, Hwayang-Dong, Sungdong-Ku, Seoul, Korea

Date: \_\_\_\_\_

Residence: Seoul, Korea  
Citizenship: Republic of Korea  
Address: 237-188, Sinsa-Dong, Eunpyung-Ku, Seoul, Korea

Date: \_\_\_\_\_

Residence: Seoul, Korea  
Citizenship: Republic of Korea  
Address: 42-45, Yeokchon-Dong, Eunpyung-Ku, Seoul, Korea

Date: \_\_\_\_\_

Residence: Seoul, Korea  
Citizenship: Republic of Korea  
Address: 30-12, Sungsan-Dong, Mapo-Ku, Seoul, Korea

more effectively performing the management of the maintenance system by providing a more accurate and reliable life span prediction of the components of the elevator and by preventing failures due to aging and abnormal friction of the components of the elevator, by more accurately predicting when the aged components must be changed.